


- 1 Substrate: 1.59mm ± 0.18mm [0.0625" ± 0.007"]
FR4/G10 or equivalent high temp material;
Non-clad
- 2 Pins: material- Brass Alloy 360 1/2 hard; finish-
0.25µm [10µ"] Au over 1.27µm [50µ"] Ni (min.).
- 3 Solder Balls: Sn63Pb37

Description: Giga-snaP BGA SMT Foot
224 position terminal pins (0.8mm centers) to SMT solder balls (BGA type). Pin assignment 1:1.

Tolerances: diameters ± 0.03mm [± 0.001"], PCB perimeters ± 0.13mm [± 0.005"], PCB thicknesses ± 0.18mm [± 0.007"], pitches (from true position) ± 0.08mm [± 0.003"], all other tolerances ± 0.13mm [± 0.005"] unless stated otherwise. Materials and specifications are subject to change without notice.

 <p>© 2009 IRONWOOD ELECTRONICS, INC. 11351 Rupp Drive, Suite 400, Burnsville, MN 55337 Tele: (952) 229-8200 www.ironwoodelectronics.com</p>	<p>SF-BGA224B-B-61 Drawing</p>	<p>Status: Released</p>	<p>Scale: 6:1</p>	<p>Rev: B</p>
	<p>Drawing: A. Evans</p>	<p>Date: 5/27/09</p>	<p>File: SF-BGA224B-B-61 Dwg.mcd</p>	<p>Modified: 09/02/14</p>