


PROPRIETARY INFORMATION
 Information contained in this drawing is confidential. Copying, distributing or use in any manner, other than that specified by IRONWOOD ELECTRONICS, INC., is strictly prohibited and may be unlawful. If you have received this drawing in error, please return to IRONWOOD ELECTRONICS, INC. at the address listed below.

All tolerances: ± 0.005 " (unless stated otherwise). Materials and specifications are subject to change without notice.

Description: Logic Analyzer Adaptor for TEKTRONIX Logic Analyzer
 255 position BGA land socket to 255 position surface mountable BGA emulator foot with high density Mictor connectors with latch housing and a 16 position JTAG connector. Pin assignment/ interconnect is configured for the PowerPC 740 microprocessor and Tektronix logic analyzer. All runs from the BGA to the Mictors have a 180 ohm resistor within a 0.500" of its BGA source.

- 1 Substrate: 0.0625" ± 0.007 " FR4/G10 or equivalent high temp material.
- 2 Pins: shell material- Brass; shell finish- 10 μ " Gold over 50 μ " Nickel (min.). Contact material- Beryllium copper; contact finish 10 μ " Gold over 100 μ " Nickel (min.)
- 3 Pins: material- Brass; finish- 10 μ " gold over 50 μ " nickel (min.).

 © 1998 IRONWOOD ELECTRONICS, INC. PO BOX 21151 ST. PAUL, MN 55121 Tele: (651) 452-8100 www.ironwoodelectronics.com	LA-BGA-740 -S-B-01 Drawing	Status: Released	Scale: 2:1	Rev: D
		Drawing: Vang Thao	Date: 2/18/98	
		File: LA-BGA-740-S-B-01 Dwg	Modified: 4/6/98, DM	