



Top View

- △1 Substrate: 0.0625"±0.007" FR4/G10 or equivalent high temp material. 1/2 oz. Cu clad. SnPb plating
- △2 Pins: Material- Brass Alloy 360 1/2 hard; finish- 10µ" Au over 50µ" Ni (min.).
- △3 Pins: shell material- Brass Alloy 360 1/2 hard; finish- 10µ" Au over 50µ" Ni (min.). Contact material- BeCu; finish 10µ" Au over 100µ" Ni (min.).
- △4 Leads: material- BeCu Alloy 194; plating- 60/40 SnPb (150-400µ")



Side View




End View

Description: CARRIER ADAPTOR:

Test Points to a 44 position J-leaded surface mount foot 44 position SOIC (0.52" body width)

All tolerances: ±0.005" (unless stated otherwise). Materials and specifications are subject to change without notice.

	CA-SO44A-N-J-T-01 Drawing	Status: Released	Scale: 1:1	Rev: A
	© 1997 IRONWOOD ELECTRONICS, INC. PO BOX 21151 ST. PAUL, MN 55121 Tele: (651) 452-8100 www.ironwoodelectronics.com	Drawing by: EVS	Date: 5/6/97	
		File: CA-SO44A-N-J-T-01 Dwg	Modified: 3/10/98	